

KRINNER
The Ground Screws


E SERIES

www.krinner.com




E SERIES

The KRINNER Ground Screw with eccentric adjustment for exact alignment



E SERIES

The KRINNER Ground Screw with eccentric adjustment for exact alignment



The E Series of ground screws can be optionally equipped with excenter to suit the application conditions. The excenter allows fine adjustment and ensures perfect vertical alignment of the erected object. The system is especially well suited to resonance- and vibration-damped installation of poles and masts.

RECOMMENDED DRIVERS:

For correct insertion of E Series ground screws, use the Ground Screw Driver **KR E 10** or **KR E 20, KR D 55** driver, or **KR B 40, KR B 60** or **KR B 250** Lot-o-Mat.

TIPS FOR INSTALLATION:

Before inserting the excenter, fill a small amount of granulate into the screw foundation. Tap the fixing ring down with a hammer before fixing with screws.

- Facilitates tightening of the excenter
- Dampens resonance and vibrations

Overview of E Series

KSF E 140x2100-E76-100	KSF E 140x1600-E76-100	KSF E 140x1300-E76-100	KSF E 89x1000-E60	KSF E 89x800-E60	KSF E 89x550-E60
Length (mm)					
2100	1600	1300	1000	800	550
Tube diameter (mm)					
139.70	139.70	139.70	88.90	88.90	88.90
Weight (kg)					
23.50	18.50	15.00	5.50	4.30	3.50
Item number					
25500	26160	25502	24100	24080	24055

